



FT



NEVUS 75

TECHNICAL DATA



230 Vac

IP44

CRI
>80/>90

CREE COB
LED

DIMMABLE
DALI/0-10V
Optional

Directional spotlight for maximum demands, ideal for general accent lighting applications, modular design, can be swiveled, standard power supply included, outer trim allows it for upgrading existing high voltage spotlights to LED, consistent color stability, low-glare optics, higher price-performance ratio, simple, rapid mounting with clip system, suitable for hotel rooms, retail, bars and restaurants.

DRIVER
CC

Standard

Lighting Control

Phase Dim.

1-10V


DALI

CRI

Standard
CRI >80

CRI >90

BEAM ANGLE



FINISH

White (WH)

Black (BK)

TECHNICAL DATA

LED	:	CREE COB LED
System Power	:	5 W
MacAdam Step	:	SDCM <3
Luminaire Efficacy	:	87 lm/W (@4000K)
Lifetime	:	L ₈₀ B ₁₀ 50,000Hrs, Ta@25°C
UGR	:	< 20

GENERAL

Mounting	:	Ceiling Recessed, Indoor
Housing	:	Aluminium
Heatsink	:	Aluminium
Lens	:	Clear
Adjustability	:	Yes
Driver Mounting	:	Remote
Emergency kit	:	Optional

IP Rating	:	IP20
Protection Class IEC	:	II
Energy Class	:	A+
Working Temp.	:	-20° to 50°C
Glow-wire test	:	650°
Weight	:	0.35 Kg
Warranty	:	3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K


www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

NEVUS 75

TECHNICAL DATA


NEVUS 75



COLOR TEMP.	POWER	CRI	LUMENS	CODE
3000K	5 W	80+	415 lm	INT20097-30K
4000K			435 lm	INT20097-40K

2700K 3000K 4000K 5000K 6000K

DIMENSION



OPTIONAL



NEVUS 85 10W
INT20096

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	