



FT






## NEVUS 85

### TECHNICAL DATA



	230 Vac	IP44	IK06	CRI >80/>90	CREE COB LED	DIMMABLE DALI/0-10V Optional
---	---------	------	------	-------------	--------------	------------------------------------

Directional spotlight for maximum demands, ideal for general accent lighting applications, modular design, can be swiveled, standard power supply included, outer trim allows it for upgrading existing high voltage spotlights to LED, consistent color stability, low-glare optics, higher price-performance ratio, simple, rapid mounting with clip system, suitable for hotel rooms, retail, bars and restaurants.

DRIVER CC	Standard	Lighting Control	Phase Dim.	1-10V	DALI
CRI	Standard	CRI >80	CRI >90		
BEAM ANGLE					
FINISH	White (WH)	Black (BK)			

#### TECHNICAL DATA

LED	: CREE COB LED
System Power	: 10 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 85 lm/W (@4000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@25°C
UGR	: <20

#### GENERAL

Mounting	: Ceiling Recessed, Indoor
Housing	: Aluminium
Heatsink	: Aluminium
Lens	: Clear
Adjustability	: Yes
Driver Mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP20
IK Rating	: IK06
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°
Weight	: 0.35 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K

FT »

# NEVUS 85

## TECHNICAL DATA


### NEVUS 85



COLOR TEMP.	POWER	CRI	LUMENS	CODE
3000K	10 W	80+	800 lm	INT20096-30K
4000K			850 lm	INT20096-40K

2700K 3000K 4000K 5000K 6000K

#### DIMENSION



#### OPTIONAL



**NEVUS 75 5W**  
INT20097

#### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	