




FT




PALAOs CIRCULAR GYPSUM Ø300

TECHNICAL DATA



	230Vac	IP44	IK07	CRI >80	DIMMABLE DALI/0-10V <i>Optional</i>
---	--------	------	------	---------	--

Special BA-13 gypsum recessed round slim panel generates uniform diffused general lighting, ultra-flat construction with visible white outer trim, homogenous light distribution without direct or reflected glare, higher visual comfort, lower glare rating values, consistent color stability, with die-cast aluminium frame, very good heat dissipation, diverse range of choice on size-wattage, delivered with remote driver, also available in square shaped panel.

DRIVER	Standard	Lighting Control Phase Dim. 1-10V DALI
CRI	Standard CRI >80	CRI >90 CRI >97
BEAM ANGLE		110°
FINISH	White (WH)	Black (BK)

TECHNICAL DATA

LED	: BRIDGELUX SMD LED
System Power	: 24 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 79 lm/W (@6000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	: < 22

GENERAL

Mounting	: Ceiling Recessed, Indoor
Housing	: Extruded aluminium body
Heatsink	: Aluminium
Diffuser	: PMMA
Adjustability	: No
Driver Mounting	: Remote
Emergency kit	: Not available

IP Rating	: IP44
IK Rating	: IK07
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 650°
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 6000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

PALAO'S CIRCULAR

GYPSUM Ø300

TECHNICAL DATA



PALAO'S CIRCULAR GYPSUM Ø300



DIMENSIONS	COLOR TEMP.	POWER	LUMENS	CODE
Ø 300 x 22	6000K	24 W	1890 lm	INT13247-60K
Ø 300 x 22	4000K		1870 lm	INT13247-40K
Ø 300 x 22	3000K		1690 lm	INT13247-30K

3000K 4000K 5000K 6000K

DIMENSION



OPTIONAL



PALAO'S ANGULAR GYPSUM

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.