



FT



PALAO DESIGN NARROW FRAME

TECHNICAL DATA



	220-240 50 Hz	PF > 0.95	IP40	CRI >80	IK07	1-10V/DALI Optional
---	------------------	--------------	------	------------	------	------------------------

State of the art LED panel having only 4mm width frame, overshadow your competitor's panels by attractive and neat looking; be able to connect one by one into different shapes, diversified installation way, low glare rating UGR<19, PMMA LGP, anti yellowing.

DRIVER
CC, 900mA, 27-55 Vdc

Standard	Lighting Control		
	Phase Dim.	1-10V	DALI

CRI

Standard			
CRI >80	CRI >90	CRI >97	

BEAM ANGLE



FINISH

White (WH)

TECHNICAL DATA

LED	:	BRIDGELUX SMD LED
System Power	:	36 W
MacAdam Step	:	SDCM <3
Luminaire Efficacy	:	100 lm/W (@4000K)
Lifetime	:	L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	:	< 22

GENERAL

Mounting	:	Ceiling Recessed, Indoor
Housing	:	Extruded aluminium body
Heatsink	:	Aluminium
Diffuser	:	PMMA
Adjustability	:	No
Driver Mounting	:	Remote
Emergency kit	:	Optional

IP Rating	:	IP40
IK Rating	:	IK07
Protection Class IEC	:	II
Energy Class	:	A+
Working Temp.	:	-20° to 55°C
Glow-wire test	:	650°
Weight	:	-
Warranty	:	3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 6000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

PALAOS DESIGN NARROW FRAME TECHNICAL DATA



PALAOS DESIGN NARROW FRAME



DIMENSIONS	COLOR TEMP.	POWER	LUMENS	CODE
595 W x 595 L x 16.7 H	4000K	36 W	3350 lm	INT13175-40K
595 W x 595 L x 16.7 H	5000K		3600 lm	INT13175-50K
295 W x 1195 L x 16.7 H	4000K		3350 lm	INT13177-40K

3000K 4000K 5000K 6000K



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 18, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.