



FT




PICOLO 8 ADJUSTABLE

TECHNICAL DATA



	200-220 Vac	IP54	PF >0.9	CRI >80/>90
---	-------------	------	---------	-------------

Mini COB LED spotlight with directional spot for ceiling recessed mounting, with different beam options, waterproof structural design ideal for damp locations, faceted highly specular reflector, rotationally symmetric narrow-medium distribution, available in fixed and adjustable versions, the spotlight head can be tilted to 25°, designed to replace halogen-based luminaires, offering low glare, due to slim design it fit in most types of ceilings.

DRIVER CC, 190mA, 33-38Vdc	Lighting Control Standard <input type="checkbox"/> Phase Dim. <input type="checkbox"/>
CRI	Standard CRI >80 <input type="checkbox"/> CRI >90 <input type="checkbox"/> CRI >97 <input type="checkbox"/>
BEAM ANGLE	
FINISH	White (WH) <input type="checkbox"/> Grey (GY) <input type="checkbox"/> Black (BK) <input type="checkbox"/>

TECHNICAL DATA

LED	: CITIZEN COB LED
System Power	: 8 W
MacAdam Step	: SDCM <2
Luminaire Efficacy	: 85 lm/W (@5000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@25°C
UGR	: <20

GENERAL

Mounting	: Ceiling Recessed, Indoor
Housing	: Die-cast aluminium
Reflector	: PC
Diffuser	: Glass
Adjustability	: Yes
Driver Mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP54
IK Rating	: IK08
Protection Class IEC	: II
Energy Class	: A++
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°
Weight	: 0.28 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K



FT »

PICOLO 8 ADJUSTABLE

TECHNICAL DATA




PICOLO 8 ADJUSTABLE



COLOR TEMP.	POWER	LUMENS	CODE
3000K	8 W	600 lm	INT04437-30K
4000K		650 lm	INT04437-40K
5000K		680 lm	INT04437-50K

2700K 3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

Updated on April 20, 2022

www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.