



FT



PIXEL GRID 15

TECHNICAL DATA


220-240V
50-60Hz

IP20

CREE LED

CRI
>80

DIMMABLE
DALI/1-10V
Optional

Innovative and elegant mini spot light for both general and accent lighting application, best in class design and modularity series from PIXEL range, minimalist design concept, compact and quality appearance, rich texture and visual impact, high quality graded micro grid thermoplastic black finish reflector design offering very low glaring (UGR<16) and maximum visual comfort, impressive chromatic quality, consistent color stability, with optional remote dimmable drivers.

DRIVER
CC, 700mA, 36Vdc

Lighting Control

Standard

Phase Dim.

1-10V

DALI


CRI

Standard

CRI >80

CRI >90

BEAM ANGLE



FINISH

White (WH)

Black (BK)

TECHNICAL DATA

LED	: CREE XPG
System Power	: 30 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 89 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@25°C
UGR	: <15

GENERAL

Mounting	: Ceiling recessed, Indoor
Housing	: Aluminium Alloy
Reflector	: Thermoplastic
Diffuser	: Optical Polymer
Adjustability	: No
Driver mounting	: Remote
Emergency kit	: Optional
IP Rating	: IP20
IK Rating	: IK04
Protection Class IEC	: III
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 0.490 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K


www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

PIXEL GRID 15

TECHNICAL DATA




PIXEL GRID 15



COLOR TEMP.	POWER	LUMENS	CODE
2700K	15 x 2 W	2460 lm	INT08060-27K
3000K		2550 lm	INT08060-30K
4000K		2670 lm	INT08060-40K

2700K 3000K 4000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 20, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.