



FT




PIXEL GRID 2

TECHNICAL DATA



	220-240V 50-60Hz	IP20	CREE LED	CRI >80	DIMMABLE DALI Optional
---	---------------------	------	----------	------------	-------------------------------------

Innovative and elegant mini spot light for both general and accent lighting application, best in class design and modularity series from PIXEL range, minimalist design concept, compact and quality appearance, rich texture and visual impact, high quality graded micro grid thermoplastic black finish reflector design offering very low glaring (UGR<15) and maximum visual comfort, impressive chromatic quality, consistent color stability, with optional remote dimmable drivers.

DRIVER CC, 700mA, 6Vdc	Lighting Control Standard <input type="checkbox"/> Phase Dim. <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	Standard <input type="checkbox"/> CRI >80 <input type="checkbox"/> CRI >90 <input type="checkbox"/>
BEAM ANGLE	
FINISH	White (WH) <input type="checkbox"/> Black (BK) <input type="checkbox"/>

TECHNICAL DATA

LED	: CREE XPG
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 85 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <15

GENERAL

Mounting	: Ceiling recessed, Indoor
Housing	: Aluminium Alloy
Reflector	: PC
Diffuser	: Glass
Adjustability	: No
Driver mounting	: Remote
Emergency kit	: Optional
IP Rating	: IP20
IK Rating	: IK04
Protection Class IEC	: III
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 0.011 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K

FT



PIXEL GRID 2

TECHNICAL DATA





PIXEL GRID 2



COLOR TEMP.	POWER	LUMENS	CODE
2700K	2 x 2 W	312 lm	INT08051-27K
3000K		320 lm	INT08051-30K
4000K		340 lm	INT08051-40K

2700K 3000K 4000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 20, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.