



FT






PIXEL GRID 1

TECHNICAL DATA



	220-240V 50-60Hz	IP20	CREE LED	CRI >80	DIMMABLE DALI Optional
---	---------------------	------	----------	------------	-------------------------------------

Innovative and elegant mini spot light for both general and accent lighting application, best in class design and modularity series from PIXEL range, minimalist design concept, compact and quality appearance, rich texture and visual impact, high quality graded micro grid thermoplastic black finish reflector design offering very low glaring (UGR<15) and maximum visual comfort, impressive chromatic quality, consistent color stability, with optional remote dimmable drivers.

DRIVER CC, 700mA, 3Vdc	Lighting Control	
	Standard	Phase Dim. DALI
C R I	Standard	
	CRI >80	CRI >90
BEAM ANGLE		
	15°	30° 45°
FINISH	White (WH) Black (BK)	
		

TECHNICAL DATA

LED	: CREE XPG
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 85 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <15

GENERAL

Mounting	: Ceiling recessed, Indoor
Housing	: Aluminium Alloy
Reflector	: PC
Diffuser	: Glass
Adjustability	: No
Driver mounting	: Remote
Emergency kit	: Optional
IP Rating	: IP20
IK Rating	: IK04
Protection Class IEC	: III
Energy Class	: A++
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 0.0604 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.


PIXEL GRID 1



COLOR TEMP.	POWER	LUMENS	CODE
2700K	2 W	156 lm	INT08048-27K
3000K		164 lm	INT08048-30K
4000K		170 lm	INT08048-40K

2700K 3000K 4000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

[illegible]

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	