



# FT



## PIXEL GRID 5

### TECHNICAL DATA



220-240V  
50-60Hz

IP20

CREE LED

CRI  
>80

DIMMABLE  
**DALI**  
Optional

Innovative and elegant mini spot light for both general and accent lighting application, best in class design and modularity series from PIXEL range, minimalist design concept, compact and quality appearance, rich texture and visual impact, high quality graded micro grid thermoplastic black finish reflector design offering very low glaring (UGR<15) and maximum visual comfort, impressive chromatic quality, consistent color stability, with optional remote dimmable drivers.

DRIVER  
CC, 700mA, 15Vdc

Lighting Control

Standard

Phase Dim.

DALI


CRI

Standard

CRI >80

CRI >90

BEAM ANGLE



FINISH

White (WH)

Black (BK)

#### TECHNICAL DATA

LED	: CREE XPG
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 89 lm/W (@4000K)
Lifetime	: L <sub>70</sub> B <sub>50</sub> 50,000Hrs, Ta@35°C
UGR	: <15

#### GENERAL

Mounting	: Ceiling recessed, Indoor
Housing	: Aluminium Alloy
Reflector	: PC
Diffuser	: Glass
Adjustability	: No
Driver mounting	: Remote
Emergency kit	: Optional
IP Rating	: IP20
IK Rating	: IK04
Protection Class IEC	: III
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 0.235 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

**2700K 3000K 4000K**



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

# PIXEL GRID 5

## TECHNICAL DATA




### PIXEL GRID 5



COLOR TEMP.	POWER	LUMENS	CODE
2700K	5 x 2 W	800 lm	INT08055-27K
3000K		850 lm	INT08055-30K
4000K		890 lm	INT08055-40K

2700K 3000K 4000K

### DIMENSION



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 20, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.