



FT





RECTA 1000

TECHNICAL DATA



	100-240 Vac	IP67	IK10	RGB (Optional)	CREE LED XP-E2	304 STAINLESS STEEL
---	-------------	------	------	----------------	----------------	---------------------

Linear ground recessed inground flush mounting wall washer, body made of AL6063 aluminium alloy molding, 304L stainless steel outer trim, high strengthened toughened glass can endure 2500Kg pressure, anodized surface treatment, with the design of increasing heat dissipation to fully ensure the stability and long lifespan, lighting head fixed at 10° tilted angle, special polarized light design can control the glare, delivered with aluminium alloy mounting case, optional model in 24vdc and RGB/RGBW.

DRIVER CC, 1050mA	Lighting Control Standard
CRI	Standard CRI >80 CRI >90
BEAM ANGLE	
FINISH	SS Finish 

TECHNICAL DATA

LED	: CREE XP-E2
MacAdam Step	: SDCM <4
Luminaire Efficacy	: 75 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	: <23

GENERAL

Mounting	: Ground recessed, Outdoor
Housing	: AL6063 aluminium alloy
Lens	: PMMA
Diffuser	: Tempered glass
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not Available

IP Rating	: IP67
IK Rating	: IK10
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -40° to 60°C
Glow-wire test	: 960°
Weight	: 5.50 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

RECTA 1000

TECHNICAL DATA



RECTA 1000 21W



COLOR TEMP.	LED QTY.	POWER	LUMENS	CODE
2700K	18 pcs.	21 W	1365 lm	EXT02108-27K-21W
3000K			1470 lm	EXT02108-30K-21W
4000K			1575 lm	EXT02108-40K-21W

RECTA 1000 28W



COLOR TEMP.	LED QTY.	POWER	LUMENS	CODE
2700K	24 pcs.	28 W	1510 lm	EXT02108-27K-28W
3000K			1820 lm	EXT02108-30K-28W
4000K			2100 lm	EXT02108-40K-28W


RECTA 1000 42W




COLOR TEMP.	LED QTY.	POWER	LUMENS	CODE
2700K	36 pcs.	42 W	2460 lm	EXT02108-27K-42W
3000K			2730 lm	EXT02108-30K-42W
4000K			3200 lm	EXT02108-40K-42W

2700K 3000K 4000K 5000K 6000K

DIMENSION



L992 x W70 x H100



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 20, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.