



# FT

# RESSY

## TECHNICAL DATA



	IP44 / IP20	UGR <12	CRI >90	CITIZEN COB LED
---	-------------	------------	------------	--------------------

Shallow deep recessed spot light makes discrete appearance, efficient ambient and accent lighting solution, designed to enhance architectural space, suitable for illuminating hotel rooms, private homes and shop interiors, wide choice of optics ensure utmost efficiency and excellent visual comfort, combined with a vast multitude of reflector finishes, recessed installation in false ceiling with 1-30mm thickness, aluminium alloy body, PMMA lens, passive heat dissipation, remote driver with lesser dimension than the cutout hole dia.


DRIVER  
CC, 350mA, 19Vdc

Lighting Control  
Standard ☐ Phase Dim. ☐ DALI ☐

CRI

Standard  
☐ CRI >80 ☐ CRI >90

BEAM ANGLE



### TECHNICAL DATA

LED : CITIZEN COB LED  
MacAdam Step : <3 SDCM  
Luminaire Efficacy : 86 lm/W (@4000K)  
Lifetime : L<sub>70</sub> B<sub>50</sub> 50,000Hrs, Ta@35°C  
UGR : <12

### GENERAL

Mounting : Ceiling recessed, Indoor  
Housing : Aluminium alloy  
Reflector : Aluminium  
Diffuser : PMMA  
Adjustability : No  
Driver mounting : Remote  
Emergency kit : Optional

IP Rating : IP44 / IP20  
IK Rating : IK04  
Protection Class IEC : III  
Energy Class : A+  
Working Temp. : -20° to 45°C  
Glow-wire test : 650°C  
Weight : 0.024 Kg  
Warranty : 3 yrs (extendable to 5 yrs)



COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	7 W	90+	534 lm	INT02041-27K
3000K			550 lm	INT02041-30K
4000K			600 lm	INT02041-40K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT



# RESSY

## TECHNICAL DATA

### FINISH

**Trim:** White (WH) - Black (BK)



**Reflector:** White (WH) - Anodized Black (AB) - Dark Chrome (DC) - White Chrome (WC) - Rose Gold (RG) - Matt Gold (MG) - Anodized Gold (AG)



WH-WH

WH-AB

WH-DC


WH-WC

WH-RG

WH-MG

WH-AG

### DIMENSION



IP44

IP20



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

<div></div>		PROJECT	
		LUMINAIRE REF.	
		QUANTITY	
		DATE	
		Contact Name	
		Mobile	
		Email	