



FT »

S-TUBE-II 8W

TECHNICAL DATA



	100-240 Vac	IP65	IK08	CRI >80/>95	CREE COB CXA1304
---	----------------	------	------	----------------	---------------------

Durable, high sturdiness and robust ceiling mounted luminaire, outstanding feature of this range is the option to have with 316L stainless steel mirror finish, with one directional or two directional options, wide choice of beam optics, extruded aluminum and die-cast aluminium housing, outdoor UV resistant powder coat finishing, 316L SS screws, fire resistant silicone seal waterproof gasket, 8mm thick toughened flush glass with trim, integrated driver, optional square version also available.


DRIVER
CC, 700mA, 6-11Vdc

Lighting Control
Standard

CRI

Standard
CRI >80 CRI >90 CRI >95

BEAM ANGLE



FINISH

White (WH) RAL9016 Grey (GY) RAL9006 Black (BK) RAL9005

TECHNICAL DATA

LED	: CREE CXA1304
System Power	: 8 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 88 lm/W (@5000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@25°C
UGR	: -

GENERAL

Mounting	: Ceiling Mounted, Outdoor
Housing	: Extruded and die-cast aluminium body
Reflector	: Aluminium
Diffuser	: Toughened glass (8mm thick)
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 650°
Weight	: 1.20 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K


S-TUBE-II 8W



COLOR TEMP.	POWER	LUMENS	CODE
3000K	2 x 4 W	2 x 315 lm	EXT05108-30K
4000K		2 x 340 lm	EXT05108-40K

3000K 4000K 5000K

DIMENSION

FINISH
(Optional)

S-TUBE-II 316L SS
MIRROR FINISH



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	

Contact Name	
Mobile	
Email	

