



FT



## SAK MINI 30

### TECHNICAL DATA



	100-240 Vac	IP66	IK10	CRI >70	NICHIA LED	125 lm/W
---	-------------	------	------	---------	------------	----------

Innovative compact and robust wall mounted lighting application, high power LED with superior performance, fade and abrasion resistant design, solid and durable structural construction, no upward spillage of light, high visual comfort, available for wiring from inside the luminaire, aluminium alloy body offering high heat dissipation, asymmetric optic lens is designed to make effective solution for floor washing, passageway and security lighting in outdoor and industrial applications.

DRIVER  
CC

Lighting Control  
Standard

CRI

Standard  
CRI >70 CRI >80

BEAM ANGLE



FINISH

Silver Grey

#### TECHNICAL DATA

LED	:	NICHIA LED
System Power	:	30 W
MacAdam Step	:	SDCM <2
Luminaire Efficacy	:	125 lm/W (@5000K)
Lifetime	:	$L_{80} B_{10}$ 50,000Hrs, Ta@35°C
UGR	:	<20

#### GENERAL

Mounting	:	Wall mounted, Outdoor
Housing	:	Cast aluminium
Heat Sink	:	Aluminium
Lens	:	Polycarbonate
Adjustability	:	No
Driver Mounting	:	Integrated
Emergency kit	:	Not available

IP Rating	:	IP66
IK Rating	:	IK10
Protection Class IEC	:	I
Energy Class	:	A++
Working Temp.	:	-20° to 55°C
Glow-wire test	:	850°
Weight	:	1.42 Kg
Warranty	:	3 yrs (extendable to 5 yrs)

4000K 5000K


[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

# SAK MINI 30

## TECHNICAL DATA




SAK MINI 30



COLOR TEMP.	POWER	LUMENS	CODE
4000K	30 W	3550 lm	EXT06077-40K
5000K		3750 lm	EXT06077-50K

4000K 5000K

DIMENSION



NOTES

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	