



FT



## STILLA 10

### TECHNICAL DATA



IP54

IK07

CRI  
>90

Recessed mini spot general and accent lighting solution, discreet and streamlined miniaturized form of design, elegance reflects with high quality finish, die-cast aluminum housing, high quality PMMA lens with toughened glass, various beam options, deep recessed optic reducing the glare level, IP rated gland, drives with remote constant current driver, best suitable for use in saunas, spas hammam, swimming pool areas, fitness centers, recreational centers.

DRIVER  
CC, 500mA, 19Vdc

Lighting Control

Standard

Phase Dim.


DALI

CRI

CRI >80

Standard  
CRI >90

BEAM ANGLE



FINISH

White (WH)

Black (BK)

#### TECHNICAL DATA

LED	: CITIZEN COB LED
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 80 lm/W (@4000K)
Lifetime	: L <sub>70</sub> B <sub>50</sub> 50,000Hrs, Ta@35°C
UGR	: <19

#### GENERAL

Mounting	: Ceiling recessed, Indoor, Outdoor
Housing	: Aluminium alloy
Reflector	: Aluminium
Diffuser	: Toughened glass
Adjustability	: No
Driver mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP54
IK Rating	: IK07
Protection Class IEC	: III
Energy Class	: A
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 0.183 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K

FT »

# STILLA 10

## TECHNICAL DATA




### STILLA 10



COLOR TEMP.	POWER	LUMENS	CODE
2700K	10 W	720 lm	INT03052-27K
3000K		750 lm	INT03052-30K
4000K		800 lm	INT03052-40K

2700K 3000K 4000K

### DIMENSION



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	



[www.switch-made.com](http://www.switch-made.com)

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.