




FT



STILLA 2

TECHNICAL DATA



	700mA	IP65	IK07	CRI >80	LUMILEDS LED
---	-------	------	------	---------	--------------

Recessed mini spot general and accent lighting solution, discreet and streamlined miniaturized form of design, elegance reflects with high quality finish, aluminum housing, high quality PMMA lens with toughened glass, various beam options, deep recessed optic reducing the glare level, IP rated gland, drives with remote constant current driver, best suitable for use in saunas, spas hammam, swimming pool areas, fitness centers, recreational centers.


DRIVER
CC, 700mA, 3Vdc

Lighting Control
Standard ☐ Phase Dim. ☐ DALI ☐

CRI

Standard
☐ CRI >80 ☐ CRI >90

BEAM ANGLE



FINISH

White (WH) ☐ Black (BK) ☐

TECHNICAL DATA

LED	:	LUMILEDS LUXEON T
MacAdam Step	:	<3 SDCM
Luminaire Efficacy	:	83 lm/W (@4000K)
Lifetime	:	L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	:	<14

GENERAL

Mounting	:	Ceiling recessed, Indoor, Outdoor
Housing	:	Aluminium
Reflector	:	Aluminium
Diffuser	:	Toughened glass
Adjustability	:	No
Driver mounting	:	Remote
Emergency kit	:	Optional

IP Rating	:	IP65
IK Rating	:	IK07
Protection Class IEC	:	III
Energy Class	:	A++
Working Temp.	:	-20° to 50°C
Glow-wire test	:	650°C
Weight	:	0.071 Kg
Warranty	:	3 yrs (extendable to 5 yrs)

2700K 3000K 4000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

STILLA - 2

TECHNICAL DATA




STILLA 2



COLOR TEMP.	POWER	CRI	LUMENS
2700K	2 W	140 lm	INT03042-27K
3000K		150 lm	INT03042-30K
4000K		165 lm	INT03042-40K

2700K 3000K 4000K

DIMENSION



Trim: White (WH) Black (BK)

Reflector: White (WH) Black (BK) Gold (GD)



WH-BK



WH-WH



WH-GD



BK-GD

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 22, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.