

FT



STILLA 7

TECHNICAL DATA



IP65

IK07

CRI
>90

Recessed mini spot general and accent lighting solution, discreet and streamlined miniaturized form of design, elegance reflects with high quality finish, die-cast aluminum housing, high quality PMMA lens with toughened glass, various beam options, deep recessed optic reducing the glare level, IP rated gland, drives with remote constant current driver, best suitable for use in saunas, spas hammam, swimming pool areas, fitness centers, recreational centers.

DRIVER
CC, 350mA, 19Vdc

Lighting Control

Standard

Phase Dim.


DALI

CRI

CRI >80

Standard
CRI >90

BEAM ANGLE



FINISH

White (WH)

Black (BK)

TECHNICAL DATA

LED	:	CITIZEN COB LED
MacAdam Step	:	<3 SDCM
Luminaire Efficacy	:	71 lm/W (@4000K)
Lifetime	:	L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	:	<14

GENERAL

Mounting	:	Ceiling recessed, Indoor, Outdoor
Housing	:	Aluminium
Reflector	:	Aluminium
Diffuser	:	Toughened glass
Adjustability	:	No
Driver mounting	:	Remote
Emergency kit	:	Optional

IP Rating	:	IP65
IK Rating	:	IK07
Protection Class IEC	:	III
Energy Class	:	A
Working Temp.	:	-20° to 50°C
Glow-wire test	:	650°C
Weight	:	0.28 Kg
Warranty	:	3 yrs (extendable to 5 yrs)

2700K 3000K 4000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.


FT »

STILLA 7

TECHNICAL DATA




STILLA 7



COLOR TEMP.	POWER	LUMENS	CODE
2700K	7 W	420 lm	INT03048-27K
3000K		446 lm	INT03048-30K
4000K		500 lm	INT03048-40K

2700K 3000K 4000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 22, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.