



FT




SWAT 3-3

TECHNICAL DATA



	220-240V 50-60Hz	IP20	CREE COB	CRI >80>90	DIMMABLE DALI <i>Optional</i>
---	---------------------	------	-------------	---------------	--

Recessed mini spot light which hides the light source but generates very efficient light that directs customers attention, good color rendering, body made of pure aluminium and is molded through extrusion, tiltable swivel lamp head (0° to 30°), optional beam angles, equipped with high efficient COB LED, best suitable for showcase lighting in jewelry, watches, luxury goods as accentuation spots.

DRIVER CC, 700mA, 3 Vdc	Standard	Lighting Control <input type="checkbox"/> Phase Dim. <input type="checkbox"/> 1-10V <input type="checkbox"/> DALI
CRI	Standard <input type="checkbox"/> CRI >80 <input type="checkbox"/> CRI >90	
BEAM ANGLE		
FINISH	<input type="checkbox"/> White (WH) <input type="checkbox"/> Grey (GY) <input type="checkbox"/> Black (BK)	

TECHNICAL DATA

LED	: CREE COB LED
System Power	: 3 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 80 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@25°C
UGR	: -

GENERAL

Mounting	: Ceiling Recessed, Indoor
Housing	: Die-cast Aluminium
Heatsink	: Aluminium
Diffuser	: PMMA
Adjustability	: Yes
Driver Mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP20
IK Rating	: IK06
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 650°
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

SWAT 3-3

TECHNICAL DATA


SWAT 3-3



COLOR TEMP.	POWER	LUMENS	CODE
2700K	3 W	192 lm	INT10006-27K
3000K		216 lm	INT10006-30K
4000K		240 lm	INT10006-40K

2700K 3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	