


FT »

VENTI 2-20W

TECHNICAL DATA

	220-240 Vac	IP65	IK08	CRI >80	CREE LED CXA2520
---	----------------	------	------	------------	---------------------

Best of the class and innovative bollard, highly homogenous, harmonious and glare-less planar light distribution, outstanding feature of this bollard is the option to have with 316L stainless steel mirror finish, higher creep resistance, extruded aluminium and die-cast aluminium housing for standard version, UV resistant powder-coat finish, stainless steel screws, fire-resistant silicone seal waterproof gasket, 4mm thick PMMA diffuser, integrated driver, optional luminaire height of 700mm, additional series on the same family with dia 200mm and 30W.

DRIVER CC, 500mA, 32-42vdc	Lighting Control Standard
CRI	Standard CRI >80 CRI >90 CRI >95
BEAM ANGLE	 360°
FINISH	<div> Grey (GY) RAL 9006 </div> <div> Mirror Finish (MF) 316L SS </div> <div> Black (BK) RAL 9005 </div>

TECHNICAL DATA

LED	: CREE CXA2520
System Power	: 20 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 58 lm/W (@5000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@25°C
UGR	: -

GENERAL

Mounting	: Surface mounted, Outdoor
Housing	: Extruded and Die-cast aluminium
Reflector	: Aluminium
Diffuser	: PMMA (4mm Thick)
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: NA

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 650°
Weight	: 7.10 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K

FT



VENTI 2-20W

TECHNICAL DATA



VENTI 2-20W



COLOR TEMP.	POWER	LUMENS	CODE
3000K	20 W	980 lm	EXT13106-30K
4000K		1100 lm	EXT13106-40K

3000K 4000K 5000K

DIMENSION



OPTIONAL



VENTI-2 316L SS
MIRROR FINISH

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	



www.switch-made.com

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.