



FT



ZETA 20 CEILING MOUNTED

TECHNICAL DATA



	100-240 Vac	IP20	IK06	CRI >80/ >90	105lm/W	DIMMABLE PHASE
---	-------------	------	------	--------------	---------	----------------

Stylish and compact LED ceiling mounted solution, ZETA range offers excellent modular combination concept in different applications and mounting possibilities, clean and robust design, high performance accent lighting solution, better visual comfort, AL6063 aluminium body with oxidation treatment provides corrosion resistance, built-in driver, possible to have different optical accessories to fulfill lighting demands.


DRIVER
CC, 520mA, 34Vdc

Lighting Control
Standard Phase Dim.

CRI

Standard
CRI >80 CRI >90

BEAM ANGLE



FINISH

White (WH) Grey (GY) Black (BK)

TECHNICAL DATA

LED	: LUMINUS COB LED
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 109 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <19

GENERAL

Mounting	: Ceiling mounted, Indoor
Housing	: Die-cast aluminium
Reflector	: PC
Diffuser	: PMMA
Adjustability	: No
Driver mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP20
IK Rating	: IK06
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 1.0 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

ZETA 20 CEILING MOUNTED

TECHNICAL DATA




ZETA 20 CEILING MOUNTED



COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	20 W	80+	2020 lm	INT07310-27K
3000K			2128 lm	INT07310-30K
4000K			2180 lm	INT07310-40K

2700K 3000K 4000K 5000K

DIMENSION



OPTIONAL



ZETA II

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email



www.switch-made.com

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.