



FT »

ZETA 30 CEILING MOUNTED

TECHNICAL DATA



	100-240 Vac	IP20	IK06	CRI >80/ >90	105lm/W	DIMMABLE PHASE
---	-------------	------	------	--------------	---------	----------------

Stylish and compact LED ceiling mounted solution, ZETA range offers excellent modular combination concept in different applications and mounting possibilities, clean and robust design, high performance accent lighting solution, better visual comfort, AL6063 aluminium body with oxidation treatment provides corrosion resistance, built-in driver, possible to have different optical accessories to fulfill lighting demands.

DRIVER CC, 730mA, 34Vdc	Lighting Control Standard <input type="checkbox"/> Phase Dim. <input type="checkbox"/> 1-10V <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	Standard <input type="checkbox"/> CRI >80 <input type="checkbox"/> CRI >90 <input type="checkbox"/>
BEAM ANGLE	
FINISH	White (WH) <input type="checkbox"/> Grey (GY) <input type="checkbox"/> Black (BK) <input type="checkbox"/>

TECHNICAL DATA

LED	: LUMINUS COB LED
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 108 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <19

GENERAL

Mounting	: Ceiling mounted, Indoor
Housing	: Die-cast aluminium
Reflector	: PC
Diffuser	: PMMA
Adjustability	: No
Driver mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP20
IK Rating	: IK06
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 1.0 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K



FT »

ZETA 30 CEILING MOUNTED



TECHNICAL DATA


ZETA 30 CEILING MOUNTED



COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	30 W	80+	3015 lm	INT07313-27K
3000K			3150 lm	INT07313-30K
4000K			3240 lm	INT07313-40K

2700K 3000K 4000K 5000K

DIMENSION



OPTIONAL



ZETA II

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	



www.switch-made.com

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.