



FT



ZETA 30 TRACK

TECHNICAL DATA



	100-240 Vac	IP20	IK06	CRI >80/>90	105lm/W
---	-------------	------	------	-------------	---------

ZETA range offers stylish and compact solution with excellent modular combination concept for different applications, lighting control accessories and mounting possibilities, aluminium body ensures better heat dissipation, stylish and compact design with integrated driver, possible to have different optical accessories to fulfill lighting demands, rotationally symmetric distribution, optional triac dimmable model, availability of wide range of glare and lighting control accessories.


DRIVER
CC, 730mA, 34Vdc

Lighting Control
Standard Phase Dim.

CRI

Standard
CRI >80 CRI >90

BEAM ANGLE



FINISH

White (WH) Grey (GY) Black (BK)

TECHNICAL DATA

LED	: LUMINUS COB LED
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 108 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <19

GENERAL

Mounting	: 3C 4wire track mounting, Indoor
Housing	: Die-cast aluminium
Reflector	: PC
Diffuser	: PMMA
Adjustability	: Yes
Driver mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP20
IK Rating	: IK06
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 1.0 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

ZETA 30 TRACK

TECHNICAL DATA




ZETA 30 TRACK



COLOR TEMP.	POWER	LUMENS	CODE
2700K	30 W	3015 lm	INT07220-27K-30W
3000K		3150 lm	INT07220-30K-30W
4000K		3240 lm	INT07220-40K-30W

2700K 3000K 4000K 5000K

DIMENSION



4-pin track adaptor

OPTIONAL



ZETA II

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	



www.switch-made.com

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.