



FT



ZETA 30 WALL MOUNTED

TECHNICAL DATA



	100-240 Vac	IP20	IK06	CRI >80/>90	105lm/W	DIMMABLE PHASE
---	-------------	------	------	-------------	---------	----------------

Stylish and compact LED wall mounted solution, ZETA range offers excellent modular combination concept in different applications and mounting possibilities, clean and robust design, high performance accent lighting solution, better visual comfort, AL6063 aluminium body with oxidation treatment provides corrosion resistance, built-in driver, possible to have different optical accessories to fulfill lighting demands.


DRIVER
CC, 730mA, 34Vdc

Lighting Control
Standard Phase Dim.

CRI

Standard
CRI >80 CRI >90

BEAM ANGLE



FINISH

White (WH) Grey (GY) Black (BK)

TECHNICAL DATA

LED	: LUMINUS COB LED
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 108 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <19

GENERAL

Mounting	: Wall mounted, Indoor
Housing	: Die-cast aluminium
Reflector	: PC
Diffuser	: PMMA
Adjustability	: Yes
Driver mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP20
IK Rating	: IK06
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 1.0 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

ZETA 30 WALL MOUNTED

TECHNICAL DATA




ZETA 30 WALL MOUNTED



COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	30 W	80+	3015 lm	INT07330-27K
3000K			3150 lm	INT07330-30K
4000K			3240 lm	INT07330-40K

2700K 3000K 4000K 5000K

DIMENSION



OPTIONAL



ZETA II

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.