



FT



## ZOOM-X 30

### TECHNICAL DATA



	200-240 Vac	IP20	CREE LED	CRI >80
---	-------------	------	----------	---------

New innovative track light with advanced zooming technology, precise stepless zooming, vivid and uniform lighting effect, changeable lighting beam angle from narrow to wide, rotationally symmetric distribution, 355° in horizontal direction and 0-90° in vertical direction, tensile aluminium body provides excellent thermal dissipation, integrated compact driver, also available in 15W/25W version.

**DRIVER**  
CC, 700mA, 25-42Vdc

**Lighting Control**  
Standard

**CRI**

Standard  
☐ CRI >80   ☐ CRI >90   ☐ CRI >97

**BEAM ANGLE**



**FINISH**

☐ White (WH)   ☐ Black (BK)

#### TECHNICAL DATA

LED	: CREE CXA 1820
System Power	: 30 W
MacAdam Step	: SDCM <2
Luminaire Efficacy	: 96 lm/W (@4000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@25°C
UGR	: <20

#### GENERAL

Mounting	: Track mounted, Indoor
Housing	: Die-cast aluminium body
Heatsink	: Aluminium
Diffuser / Lens	: Optical Polymer
Adjustability	: Yes
Driver Mounting	: Integrated
Track System	: 3C 4 Wire

IP Rating	: IP20
IK Rating	: IK06
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 45°C
Glow-wire test	: 650°
Weight	: 1.30 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

**2700K 3000K 4000K 5000K**

FT »

# ZOOM-X 30

## TECHNICAL DATA





ZOOM-X 30



COLOR TEMP.	POWER	LUMENS	CODE
2700K	30 W	2550 lm	INT03008
3000K		2670 lm	INT03009
4000K		2880 lm	INT03010

2700K 3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.