



FT




## ZOOM-X 20

### TECHNICAL DATA



	200-240 Vac	IP20	CREE LED	CRI >80
---	-------------	------	----------	---------

New innovative track light with advanced zooming technology, precise stepless zooming, vivid and uniform lighting effect, changeable lighting beam angle from narrow to wide, rotationally symmetric distribution, 355° in horizontal direction and 0-90° in vertical direction, tensile aluminium body provides excellent thermal dissipation, integrated compact driver, also available in 15W/25W version.

DRIVER	Lighting Control Standard
CRI	Standard <div>CRI &gt;80</div> <div>CRI &gt;90</div> <div>CRI &gt;97</div>
BEAM ANGLE	
FINISH	<div>White (WH)</div> <div>Black (BK)</div>

#### TECHNICAL DATA

LED	: CREE CXA1512
System Power	: 20 W
MacAdam Step	: SDCM <2
Luminaire Efficacy	: 94 lm/W (@4000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@25°C
UGR	: <20

#### GENERAL

Mounting	: Track mounted, Indoor
Housing	: Die-cast aluminium body
Heatsink	: Aluminium
Diffuser / Lens	: Optical Polymer
Adjustability	: Yes
Driver Mounting	: Integrated
Track System	: 3C 4 Wire

IP Rating	: IP20
IK Rating	: IK06
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 45°C
Glow-wire test	: 650°
Weight	: 1.00 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

# ZOOM-X 20

## TECHNICAL DATA





ZOOM-X 20



COLOR TEMP.	POWER	LUMENS	CODE
2700K	20 W	1700 lm	INT03005
3000K		1780 lm	INT03006
4000K		1880 lm	INT03007

2700K 3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.