



FT »


LINE E2513

TECHNICAL DATA



Code: PRE2513
Functional Lighting: Interior, office, shop, schools, tertiary
Lifetime: 50,000 hrs.
Working Temperature: -20°C to +45°C
Heat Dissipation: Max. 15W/m
CCT: 2700K / 3000K / 4000K / 6000K
Beam Angle: 110°
Material: Aluminium 6063-T5 (Oxidized silver)
Diffuser: PC
Weight: 0.5 Kg / 2.5 m
Process: Anodic Oxidation / Powder
3 Years Warranty

DIMENSION



Length:
2504mm (Incl. endcap)

Accessories Included




Alu. Profile/
Diffuser



End Caps x 2

(for 2500mm)

FINISH





Profile Cutting Calculation

$$L_{min} = (1 \times 50mm) + (2 \times 6mm) + 8mm \text{ } \textcircled{1} = 70mm$$

$$L_{max} = (39 \times 50mm) + (2 \times 6mm) + 8mm \text{ } \textcircled{1} = 1970mm$$

Recommended grooving size:

Cutout: W=18mm, H=13mm



●● TECHNICAL CHARACTERISTICS



LED STRIP

INPUT VOLTAGE	IP	CCT	CRI	W/M	LEDS/M	CUTTING UNIT (MM)	LAMP LUMEN/M @CRI 90	LUMINAIRE LUMEN/M @CRI 90	DIMENSION (MM)	CODE
24Vdc	IP33	4000K	>90	6.6 W/m	140	50mm (7 LEDs)	590 lm/m	500 lm/m	5000 x 8 x 1.2	-

CCT: **2700K** **3000K** **4000K** **6000K**




LED DRIVER

OUTPUT VOLTAGE	TYPE	IP	POWER	MOUNTING	DIMENSION (MM)	CODE
24Vdc	DIMMABLE 0-10V	IP20	*30W	Remote	230 x 30 x 21	-

**Please consult us for more choice of LED driver*

●● OPTIONAL ACCESSORIES



End Cap With Hole
E2513-ECS-H



Recessed Clip
E5213-CP

●● STRUCTURE




Accessories Included

- 1. Aluminium Profile
- 2. Diffuser
- 3. End caps (S0709-EC)


Optional Accessories

- 4. Mounting bracket (S0709-BK)
- 5. LED Lighting Source

●● APPLICATIONS




●● WIRING DRAWING



Connection order of 5Pin wire:
 Brown: L
 Blue: N
 Green: GND
 Red: 0-10V+
 Black: 0 10V

●● INSTALLATION



NOTES

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	