



FT »


LINE E5535

TECHNICAL DATA



- Code:** PRE5535
- Functional Lighting:** Interior, office, shop, schools, tertiary
- Lifetime:** 50,000 hrs.
- Working Temperature:** -20°C to +45°C
- Heat Dissipation:** Max. 33W/m
- CCT:** 2700K/ 3000K/ 4000K/ 5000K/ 6000K
- Beam Angle:** 110°
- Material:** Aluminium 6063-T5 (Oxidized silver)
- Diffuser:** PC
- Weight:** 2.60 Kg / 2.5 m
- Process:** Anodic Oxidation / Powder
- 3 Years Warranty**

DIMENSION



Length:
2520mm (incl. endcap)

FINISH

White (WH) RAL 9003 Aluminium (AL) Black (BK) RAL 9005



(Standard)

Accessories Included



Alu. Profile/
Diffuser



End Caps X 2


(for 2500mm)

Profile Cutting Calculation

$$L_{min} = (1 \times 50mm) + (2 \times 10mm) = 70mm$$

$$L_{max} = (50 \times 50mm) + (2 \times 10mm) = 2520mm$$


Cutout: 2509 x 44mm



●● TECHNICAL CHARACTERISTICS



OR



FLEX ROLL

| INPUT VOLTAGE | IP | CCT | W/M | LEDS/M | CUTTING UNIT (MM) | LAMP LUMEN/M @CRI 80 | LUMINAIRE LUMEN/M @CRI 80 | DIMENSION (MM) | CODE |
|---------------|------|-------|--------|--------|-------------------|----------------------|---------------------------|-----------------|-----------|
| 24Vdc | IP33 | 4000K | 20 W/m | 280 | 50 (14 LED) | 2706 lm/m | 2300 lm/m | 2500 x 20 x 1.5 | FR8280-20 |

CCT: **2700K** **3000K** **4000K** **5000K** **6000K** CRI: >80 >95

LED PCB

| INPUT VOLTAGE | IP | CCT | W/M | LEDS/M | CUTTING UNIT (MM) | LAMP LUMEN/M @CRI 80 | LUMINAIRE LUMEN/M @CRI 80 | DIMENSION (MM) | CODE |
|---------------|------|-------|--------|--------|-------------------|----------------------|---------------------------|----------------|------------|
| 24Vdc | IP33 | 4000K | 20 W/m | 280 | 50 (14 LED) | 2706 lm/m | 2300 lm/m | 499 x 23 x 5.6 | PCB8280-23 |

CCT: **2700K** **3000K** **4000K** **5000K** **6000K** CRI: >80 >95



LED DRIVER

| OUTPUT VOLTAGE | TYPE | IP | POWER | MOUNTING | DIMENSION (MM) | CODE |
|----------------|----------------|------|-------|----------|----------------|------|
| 24Vdc | DIMMABLE 0-10V | IP20 | *60W | Remote | 285 x 30 x 21 | - |

**Please consult us for more choice of LED driver*

●● OPTIONAL ACCESSORIES



Recessed Buckle (N-shaped)
E5535-RN



Recessed Buckle (Butterfly)
E5535-RB



180° Extender
E5535-180



"L" Type Light Corner
E5535-L90



"L" Type Light Corner (Inner)
E5535-L90N



"L" Type Light Corner (Exterior)
E5535-L90W



"T" Type Light Corner
E5535-T90




"X" Type Light Corner
E5535-X90




●● APPLICATIONS




Recessed (Butterfly)



Recessed (N-shaped)





●● WIRING DRAWING



Connection order of 5Pin wire:
 Brown: L
 Blue: N
 Green: GND
 Red: 0-10V+
 Black: 0 10V

●● INSTALLATION



NOTES

| | |
|----------------|--|
| PROJECT | |
| LUMINAIRE REF. | |
| QUANTITY | |
| DATE | |