

FT »

LINE T60

TECHNICAL DATA



- Code:** PRT60
- Functional Lighting:** Interior, office, shop, schools, tertiary
- Lifetime:** 50,000 hrs.
- Working Temperature:** -20° C to +45° C
- Heat Dissipation:** Max. 25W/m
- CCT:** 2700K / 3000K/ 4000K/ 5000K/ 6000K
- Beam Angle:** 110°
- Material:** Aluminium 6063-T5 (Oxidized silver)
- Diffuser:** PC
- Weight:** 1.0 Kg / 2.5 m
- Process:** Anodic Oxidation / Powder
- 3 Years Warranty**

Accessories Included



Alu. Profile/
Diffuser



End Caps x 2

(for 2500mm)

DIMENSION



Length:
2504mm (Incl. endcap)




FINISH



(Standard)

Profile Cutting Calculation



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

●● TECHNICAL CHARACTERISTICS



LED STRIP

INPUT VOLTAGE	IP	CCT	CRI	W/M	LEDS/M	CUTTING UNIT (MM)	LAMP LUMEN/M @CRI 80	LUMINAIRE LUMEN/M @CRI 80	DIMENSION (MM)	CODE
24Vdc	IP33	4000K	>80	20 W/m	280	50mm (14 LED)	2706 lm/m	2300 lm/m	2500 x 20 x 1.5	-

CCT: **2700K** **3000K** **4000K** **5000K** **6000K**



LED DRIVER

OUTPUT VOLTAGE	TYPE	IP	POWER	MOUNTING	DIMENSION (MM)	CODE
24Vdc	DIMMABLE 0-10V	IP20	*60W	Remote	285 x 30 x 21	-

**Please consult us for more choice of LED driver*

●● OPTIONAL ACCESSORIES



Suspension Kit with Junction box
T60-PY




Suspension Kit
T60-PN



180°-Extender
T60-EX09


●● STRUCTURE





Accessories Included

1. Aluminium Profile
2. Diffuser
3. End caps
4. LED Lighting source
5. Suspension kit

● ● WIRING DRAWING



● ● INSTALLATION



NOTES

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	