




FT




PIKI 33

TECHNICAL DATA



	24Vdc	IP66	IK04	CRI >80	CREE LED
---	-------	------	------	---------	----------

Rotationally symmetric High power COB LED spot light, honey comb louvre reducing the glare values, for maximum quality of light and best visual comfort, aluminium alloy body, tempered glass, high purity aluminum reflector, high heat dissipation, longer service life, optional model with cylindrical hood, spike accessory, also available in 1W.

DRIVER	CV, 24V	Lighting Control Standard ON/OFF
CRI	Standard CRI >80	
BEAM ANGLE		
FINISH	<div> <div>Black (BK)</div> <div>Silver (SL)</div> </div>	
	(Standard)	

TECHNICAL DATA

LED	: CREE LED
System Power	: 2 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 88 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	: <22

GENERAL

Mounting	: Surface mounted, Outdoor
Housing	: CNC 6063# Aluminium
Lens	: Optical Lens
Diffuser	: Tempered glass. T=4mm
Spike	: ABS
Adjustability	: Yes
Driver mounting	: Remote
Emergency kit	: Not available

IP Rating	: IP66
IK Rating	: IK04
Protection Class IEC	: III
Energy Class	: A+
Working Temp.	: -30° to 50°C
Glow-wire test	: 650°C
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 5700K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.


PIKI 33



COLOR TEMP.	POWER	LUMENS	CODE
2700K	2 W	160 lm	EXT19090-27K
3000K		170 lm	EXT19090-30K
4000K		176 lm	EXT19090-40K

2700K 3000K 4000K 5000K 5700K

DIMENSION



ACCESSORIES (Optional)



SPIKE
(to be ordered separately)
ACC99045



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

[illegible]

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	

Contact Name	
Mobile	
Email	