




FT



## PIKI 55

### TECHNICAL DATA



	AC 220-240V	IP66	IK04	CRI >80	CREE LED
---	----------------	------	------	------------	----------

Rotationally symmetric High power COB LED spot light, maximum quality of light and visual comfort, aluminium alloy body, tempered glass, high purity aluminum reflector, high heat dissipation, longer service life, optional model with cylindrical hood, spike accessory, also available in 4W.


DRIVER  
CV, 24V

Lighting Control  
Standard ON/OFF

CRI

Standard  
CRI >80

BEAM ANGLE



FINISH

Black (BK)

(Standard)

#### TECHNICAL DATA

LED	: CREE LED
System Power	: 7 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 88 lm/W (@4000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@35°C
UGR	: <22

#### GENERAL

Mounting	: Surface mounted, Spike Mounted, Outdoor
Housing	: CNC 6063# Aluminium
Lens	: Optical Lens
Diffuser	: Tempered glass. T=4mm
Spike	: ABS
Adjustability	: Yes
Driver mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP66
IK Rating	: IK04
Protection Class IEC	: III
Energy Class	: A+
Working Temp.	: -30° to 50°C
Glow-wire test	: 650°C
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 5700K


## PIKI 55



COLOR TEMP.	POWER	LUMENS	CODE
2700K	7 W	560 lm	EXT19094-27K
3000K		595 lm	EXT19094-30K
4000K		616 lm	EXT19094-40K

2700K 3000K 4000K 5000K 5700K

## DIMENSION




PIKI 55 CYLINDRICAL HOOD  
EXT19095

PIKI 55 CYLINDRICAL HOOD 45D  
EXT19096

(Optional)

### ACCESSORIES (Optional)



SPIKE  
(to be ordered separately)  
ACC99046



## NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

[illegible]

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	

Contact Name	
Mobile	
Email	