



FT »


PIKI 69

TECHNICAL DATA



	AC 220-240V	IP66	IK04	CRI >80	CREE LED
---	----------------	------	------	------------	----------

Rotationally symmetric high power COB LED spot light, for maximum quality of light and best visual comfort, aluminium alloy body, tempered glass, high purity aluminum reflector, high heat dissipation, longer service life, optional model with cylindrical hood to reduce glare values, spike accessory, also available in 8W.

DRIVER CV, 24V	Lighting Control Standard ON/OFF
CRI	Standard CRI >80
BEAM ANGLE	
FINISH	Black (BK) Silver (SL) (Standard)

TECHNICAL DATA

LED	: CREE LED
System Power	: 10 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 88 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	: <22

GENERAL

Mounting	: Surface mounted, Outdoor
Housing	: CNC 6063# Aluminium
Lens	: Optical Lens
Diffuser	: Tempered glass. T=4mm
Spike	: ABS
Adjustability	: Yes
Driver mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP66
IK Rating	: IK04
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -30° to 50°C
Glow-wire test	: 650°C
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 5700K



FT »

PIKI 69

TECHNICAL DATA




PIKI 69



COLOR TEMP.	POWER	LUMENS	CODE
2700K	10 W	800 lm	EXT19097-27K
3000K		850 lm	EXT19097-30K
4000K		880 lm	EXT19097-40K

2700K 3000K 4000K 5000K 5700K

DIMENSION




PIKI 69 CYLINDRICAL HOOD
EXT19098



PIKI 69 CYLINDRICAL HOOD 45D
EXT19099

(Optional)

ACCESSORIES
(Optional)



SPIKE
(to be ordered separately)
ACC99046



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on October 26, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.