




FT



PIKI 85

TECHNICAL DATA



	AC 220-240V	IP66	IK04	CRI >80	CREE LED
---	----------------	------	------	------------	----------

Rotationally symmetric High power COB LED spot light, maximum quality of light and visual comfort, aluminium alloy body, tempered glass, high purity aluminum reflector, high heat dissipation, longer service life, optional model with cylindrical hood, spike accessory, also available in 8W and 10W


DRIVER
CV, 24V

Lighting Control
Standard ON/OFF

CRI

Standard
CRI >80

BEAM ANGLE



FINISH

Black (BK)

(Standard)

TECHNICAL DATA

LED	: CREE LED
System Power	: 15 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 88 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	: <22

GENERAL

Mounting	: Surface mounted, Spike Mounted, Outdoor
Housing	: CNC 6063# Aluminium
Lens	: Optical Lens
Diffuser	: Tempered glass. T=4mm
Spike	: ABS
Adjustability	: Yes
Driver mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP66
IK Rating	: IK04
Protection Class IEC	: III
Energy Class	: A+
Working Temp.	: -30° to 50°C
Glow-wire test	: 650°C
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 5700K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.


PIKI 85



Color Temp.	Power	Lumens	Code
2700K	15 W	1200 lm	EXT19091-27K
3000K		1275 lm	EXT19091-30K
4000K		1320 lm	EXT19091-40K

2700K 3000K 4000K 5000K 5700K

DIMENSION




PIKI 85 CYLINDRICAL HOOD
EXT19101



PIKI 85 CYLINDRICAL HOOD 45D
EXT19102

(Optional)

ACCESSORIES (Optional)



SPIKE
(to be ordered separately)
ACC99046



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

[illegible]

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	